

# QuiQ 912 On-Board Industrial Battery Charger

STANDARD  
FEATURES

**Universal AC Input**

\*110-240VAC (IEC320/C14 connector)

**10-segment LED Display**

\*AC Power, 80% Charge, 100% Charge, Fault, and Ammeter (6)

**Charge Any Battery**

\*Flooded, AGM, GEL, and Lithium

\*Stores up to 10 user-selectable charge algorithms

**Sealed Design**

\*IP66 rating protects from dirt & moisture

**DC Output • 6' (1.8m) Harness**

\*3/8" Over Molded Ring Terminals

\*Battery Temp Sensor & Interlock Wire

**Optional**

\*10' Remote LED (*Dashboard Status Indicator*)



QuiQ with Optional Remote LED

**STANDARD MODELS**

912-2400	24 volt / 25 amp
912-3600	36 volt / 21 amp
912-4800	48 volt / 18 amp
912-7200	72 volt / 12 amp
912-9600	96 volt / 8.5 amp



QuiQ Programmer

**STANDARD MODELS WITH LED**

912-2400-03	24 volt / 25 amp
912-3600-D1	36 volt / 21 amp
912-4800-D1	48 volt / 18 amp
912-7200-D1	72 volt / 12 amp
912-7200-M1	72 volt / 12 amp (reverse interlock)



10' AC Cord

**ACCESSORIES & SERVICE ITEMS**

AC Cord - 10'	10' AC Cord
AC Cord - 15'	15' AC Cord
900-0002	Thermistor Repair Kit
900-0060	Temp Sensor Replacement
900-0058	Remote LED Replacement
900-0061	Remote LED Label
900-0089-02	QuiQ Programmer



Thermistor Repair Kit