



SUGGESTED CUSTOMER PRICES - ALL PRICES QUOTED EXCHANGE

PART NUMBER	TERMINAL	CORE CLASS	BIN NUMBER	NOMINAL	RATED AH	CURRENT @	MAXIMUM DIMENSIONS INCHES			HT. OF TERMINAL	WARRANTY MOS.
				VOLTAGE V	CAPACITY 20HR	20hr RATE mA	LENGTH	WIDTH	HEIGHT		
GENERAL PURPOSE DESIGN / PS DERIES											
PS-260	F1	M	PS3265	2	6.0	300	1.97	1.34	3.94	4.13	6
PS-445	F2	M	PS1492	4	4.5	225	1.89	2.09	3.70	3.86	6
PS-490	F2	M	PS2772	4	9.0	450	4.01	1.73	3.74	4.02	6
PS-4100	F1	M	PS3084	4	10.0	500	4.01	1.97	3.70	3.85	6
PS-605W	WL	M	PS3218	6	0.5	25	2.24	0.55	1.97	1.97	6
PS-610	F1	M	PS967	6	1.1	55	2.00	1.65	2.00	2.20	6
PS-612	F1	M	PS877	6	1.4	70	3.82	0.94	2.00	2.20	6
PS-628	F1	M	PS1942	6	2.9	145	2.60	1.30	3.86	4.06	6
PS-630	F1	M	PS1375	6	3.5	175	5.28	1.34	2.35	2.56	6
PS-632	F1	M	PS2802	6	3.5	175	2.60	1.30	4.65	4.80	6
PS-640	F1	M	PS1074	6	4.5	225	2.76	1.86	3.94	4.25	6
PS-650LF	F1	M	PS2079	6	5.0	250	2.64	2.64	3.94	4.64	6
PS-650LS	SP	M	PS2079	6	5.0	250	2.64	2.64	3.94	4.64	6
PS-665FP	FP	M	PS2644	6	6.5	325	3.86	2.20	3.78	4.02	6
PS-670	F1	M	PS1796	6	7.0	350	5.95	1.34	3.70	3.94	6
PS-682F1	F1	M	PS2849	6	9.0	450	3.86	2.20	4.65	4.72	6
PS-6100F1	F1	M	PS2843	6	12.0	600	5.95	2.00	3.70	3.86	6
PS-6100F2	F2	M	PS2843	6	12.0	600	5.95	2.00	3.70	3.86	6
PS-6120FP	FP	M	PS3061	6	13.0	650	4.25	2.80	5.55	5.55	6
PS-6200	NB1	M	PS6208	6	20.0	1000	6.18	3.27	4.92	4.92	6
PS-6360F2	F2	M	PS8100	6	36.0	1800	6.25	3.35	6.50	6.93	6
PS-6360NB	NB1	M	PS8100	6	36.0	1800	6.25	3.35	6.50	6.93	6
PS-62000	T8	M	PS37676	6	210.0	10500	12.05	6.65	8.65	8.96	6
PS-832	F1	M	PS2762	8	3.2	160	5.29	1.42	2.49	2.70	6
PS-1208W	WL	M	PS2847	12	0.8	40	3.78	0.98	2.44	n/a	6
PS-1212	F1	M	PS2010	12	1.4	70	3.78	1.69	2.04	2.28	6
PS-1220	F1	M	PS2378	12	2.5	125	7.00	1.38	2.36	2.56	6
PS-1221S	F1/0	M	PS3627	12	2.0	100	5.91	0.80	3.52	n/a	6
PS-1223	PC	M	PS4215	12	2.3	115	7.17	0.94	2.40	2.40	6
PS-1227	F1	M	PS2356	12	2.9	145	3.11	2.20	3.90	4.13	6
PS-1228	F1	M	PS2461	12	2.8	140	5.24	1.30	3.82	4.09	6
PS-1229	F1	M	PS4057	12	2.9	145	7.00	1.38	2.36	2.60	6
PS-1230	F1	M	PS2808	12	3.4	170	5.24	2.64	2.36	2.60	6
PS-1238	F1	M	PS3338	12	3.8	190	7.68	1.85	2.91	2.99	6
PS-1250F1	F1	M	PS2470	12	5.0	250	3.54	2.76	3.98	4.21	6
PS-1250F2	F2	M	PS2470	12	5.0	250	3.54	2.76	3.98	4.21	6
PS-1270F1	F1	M	PS3245	12	7.0	350	5.95	2.56	3.70	3.86	6
PS-1270F2	F2	M	PS3245	12	7.0	350	5.95	2.56	3.70	3.86	6
PS-1280F1	F1	M	PS3252	12	8.0	400	5.95	2.56	3.72	3.94	6
PS-1280F2	F2	M	PS3252	12	8.0	400	5.95	2.56	3.72	3.94	6
PS-1282LF1	F1	M	PS5152	12	9.0	450	7.72	2.20	4.65	4.65	6
PS-1282SF1	F1	M	PS5152	12	9.0	450	3.86	4.40	4.65	4.65	6
PS-1290F2	F2	M	PS3732	12	9.0	425	5.95	2.56	3.70	3.86	6
PS-12100F1	F1	M	PS5381	12	12.0	600	5.95	4.00	3.70	3.86	6
PS-12100F2	F2	M	PS5381	12	12.0	600	5.95	4.00	3.70	3.86	6
PS-12120F2	F2	M	PS4672	12	12.0	600	5.95	3.86	3.70	3.94	6
PS-12120L	FP	M	PS6361	12	12.0	600	8.45	2.75	5.75	5.75	6
PS-12140	F2	M	PS5437	12	14.0	700	5.95	3.86	3.70	3.94	6
PS-12180F2	F2	M	PS6753	12	18.0	900	7.13	3.00	6.59	6.59	6
PS-12180NB	NB2	M	PS6753	12	18.0	900	7.13	3.00	6.59	6.59	6
PS-12180B	T12	M	PS6753	12	18.0	900	7.13	3.00	6.59	6.59	6

The product descriptions, specifications and pricing were correct at the time this material was being prepared for printing. Our policy is one of continuous development and we reserve the right to change design, specifications or pricing at any time, without notice and without incurring obligation.



SUGGESTED CUSTOMER PRICES - ALL PRICES QUOTED EXCHANGE

PART NUMBER	TERMINAL	CORE CLASS	BIN NUMBER	NOMINAL VOLTAGE V	RATED AH CAPACITY 20HR	CURRENT @ 20hr RATE mA	MAXIMUM DIMENSIONS INCHES				WARRANTY MOS.
							LENGTH	WIDTH	HEIGHT	HT. OF TERMINAL	
GENERAL PURPOSE DESIGN / PS SERIES											
PS-12260F2	F2	M	PS9006	12	26.0	1300	6.56	6.97	4.92	4.92	6
PS-12260NB	NB2	M	PS9006	12	26.0	1300	6.56	6.97	4.92	4.92	6
PS-12260B	T12	M	PS9006	12	26.0	1300	6.56	6.97	4.92	4.92	6
PS-12280	NB1	M	PS10915	12	28.0	1400	6.50	4.92	6.97	6.97	6
PS-12330NB	NB3	M	PS11624	12	33.0	1650	7.72	5.14	6.22	7.00	6
PS-12350NB	NB3	U	PS12312	12	35.0	1750	7.72	5.14	6.22	7.00	6
PS-12350B	T6	U	PS10878	12	35.0	1750	7.72	5.14	6.22	7.00	6
PS-12400	NB4	U	PS14780	12	40.0	2000	7.76	6.50	6.69	6.69	6
PS-12550U	U	A	PS20643	12	55.0	2750	9.04	5.45	8.15	8.98	6
PS-12550B	T6	A	PS20643	12	55.0	2750	9.04	5.45	8.15	8.98	6
PS-12750U	U	A	PS26846	12	75.0	3750	10.25	6.60	8.15	8.98	6
PS-12750B	T6	A	PS26846	12	75.0	3750	10.25	6.60	8.15	8.98	6
PS-121000U	U	A	PS31568	12	100.0	5000	12.00	6.60	8.15	8.98	6
PS-121000B	T6	A	PS31568	12	100.0	5000	12.00	6.60	8.15	8.98	6
PS-121100B	T11	B	PS36229	12	110.0	5500	13.00	6.73	8.35	8.66	6
PS-121400FR	T11	B	PS57977	12	140.0	7000	13.00	6.73	10.80	11.15	6
HIGH-RATE DISCHARGE DESIGN / PSH SERIES											
PSH-1255F2-FR	F2	M	PS3170	12	6.0	300	3.54	2.76	3.98	4.21	6
PSH-1280F2-FR	F2	M	PS3873	12	8.5	425	5.94	2.56	3.70	3.86	6
PSH-12100F2-FR	F2	M	PS4958	12	8.5	425	5.94	2.56	3.70	3.86	6
PSH-12180NB-FR	NB2	M	PS7823	12	21.0	1050	7.14	3.03	6.59	6.59	6

The product descriptions, specifications and pricing were correct at the time this material was being prepared for printing. Our policy is one of continuous development and we reserve the right to change design, specifications or pricing at any time, without notice and without incurring obligation.

F1 **FASTON**
0.187" x 0.032"
quick disconnect tabs.

F2 **FASTON**
0.250" x 0.032"
quick disconnect tabs

FP **FASTON POLARIZED**
Positive: "F2", Negative: "F1"

F1/0 6 | 4.8 | 0.6 | 21

SP **SPRING TERMINALS**
Fully collapsible positive and negative contacts

TH **TOY BATTERY CONNECTORS**
H-connector PS-6120 TH

TS **TOY BATTERY CONNECTORS**
S-connector PS-6120 TS

PC **PRESSURE CONTACTS**

WL **INSULATED WIRE LEADS**
• Molex Housing 5264-02 & 5263-PBT plug on PS-605
• AMP Housing 1-480318-0 & 8116-1 on PS-1208

NB1 12 | 4.8 | 12 | 2 | 5.6 | 2.1
Torque: 2.0~3.0 Nxm

NB2 14 | 4.5 | 13 | 2 | 6 | 2.1
Torque: 3.9~5.4 Nxm

NB3 16.5 | 7 | 16 | 6 | 6 | 2.1
Torque: 3.9~5.4 Nxm

NB4 15 | 7.5 | 18 | 5.5 | 6 | 2.1
Torque: 3.9~5.4 Nxm

U 17.4 | 15.9 | 13 | 19 | 22 | 18 | 22 | 18 | 13 | 13 | 9
Positive Negative
Torque: 11.0~14.7 Nxm

T6 **THREADED INSERT - 6mm STUD**
 16mm | M6 | 6mm
Torque: 3.9~5.4 Nxm

T8 **THREADED INSERT - 6mm STUD**
 20mm | M6 | 6mm
Torque: 3.9~5.4 Nxm

T11 **THREADED INSERT - 8mm STUD**
 20mm | M8 | 7mm
Torque: 11.0~14.7 Nxm

T12 **THREADED INSERT - 5mm STUD**
 12mm | M5 | 6mm
Torque: 2.0~3.0 Nxm