



| BCI GROUP SIZE | PART NUMBER | CORE CLASS | BIN NUMBER | RESERVE CAPACITY @ | | | AMPERE HOUR | | | | Kwh | VOLTAGE | MAXIMUM DIMENSIONS | | | WEIGHT LBS | WARRANTY MOS. |
|----------------|-------------|------------|------------|--------------------|-----|-----|-------------|-------|-------|--------|-----|---------|--------------------|-------|--------|------------|---------------|
| | | | | 25A | 56A | 75A | 5 HR | 10 HR | 20 HR | 100 HR | | | LENGTH | WIDTH | HEIGHT | | |

TROJAN DEEP CYCLE 6 VOLT FLOODED

| | | | | | | | | | | | | | | | | | |
|------|------------|---|---------|-----|---|-----|-----|-----|-----|-----|------|---|----------|-------|--------|-----|----|
| GC2 | T-605 | C | TB15652 | 383 | - | 105 | 175 | 193 | 210 | 232 | 1.39 | 6 | 10 3/8 | 7 1/8 | 10 7/8 | 58 | 12 |
| GC2 | T-105 | C | TB18099 | 447 | - | 115 | 185 | 207 | 225 | 250 | 1.50 | 6 | 10 3/8 | 7 1/8 | 10 7/8 | 62 | 18 |
| GC2 | T-125 | C | TB20923 | 488 | - | 132 | 195 | 221 | 240 | 266 | 1.60 | 6 | 10 1/4 | 7 1/8 | 11 1/6 | 66 | 12 |
| GC2H | T-145 | C | TB24700 | 530 | - | 145 | 215 | 239 | 260 | 287 | 1.72 | 6 | 10 1/4 | 7 1/8 | 11 7/8 | 72 | 12 |
| DIN | TE35 | C | TB24903 | 500 | - | 135 | 200 | 225 | 245 | 271 | 1.63 | 6 | 9 5/8 | 7 1/2 | 10 7/8 | 68 | 12 |
| 901 | J250G | D | TB22004 | 475 | - | 130 | 195 | 216 | 235 | 261 | 1.57 | 6 | 11 1/2 | 7 | 11 7/8 | 67 | 12 |
| 901 | J250P | D | TB26052 | 540 | - | 135 | 215 | 230 | 250 | 278 | 1.67 | 6 | 11 11/16 | 7 | 11 1/2 | 72 | 12 |
| 902 | J305E-AC | D | TB25826 | 645 | - | 160 | 250 | 280 | 305 | 339 | 2.03 | 6 | 12 1/4 | 7 | 14 3/8 | 83 | 12 |
| 902 | J305G-AC | D | TB29168 | 678 | - | 175 | 258 | 290 | 315 | 350 | 2.10 | 6 | 12 1/4 | 7 | 14 3/8 | 88 | 12 |
| 902 | J305P-AC | D | TB31513 | 711 | - | 195 | 271 | 304 | 330 | 367 | 2.20 | 6 | 11 5/8 | 7 | 14 3/8 | 96 | 12 |
| 902 | J305H-AC | D | TB35265 | 781 | - | 215 | 295 | 331 | 360 | 400 | 2.40 | 6 | 11 5/8 | 7 | 14 3/8 | 98 | 12 |
| 903 | L16E-AC | D | TB30508 | 766 | - | 185 | 303 | 340 | 370 | 411 | 2.47 | 6 | 12 1/4 | 7 | 16 3/8 | 99 | 12 |
| 903 | L16G-AC | D | TB34239 | 789 | - | 200 | 320 | 359 | 390 | 433 | 2.60 | 6 | 12 1/4 | 7 | 16 3/8 | 101 | 12 |
| 903 | L16P-AC | D | TB37855 | 850 | - | 220 | 344 | 386 | 420 | 467 | 2.80 | 6 | 11 5/8 | 7 | 16 3/4 | 114 | 12 |
| 903 | L16H-AC | D | TB41950 | 935 | - | 245 | 357 | 400 | 435 | 483 | 2.89 | 6 | 11 5/8 | 7 | 16 3/4 | 125 | 12 |
| 903 | L16P ("L") | D | TB37855 | 850 | - | 220 | 344 | 386 | 420 | 467 | 2.80 | 6 | 11 5/8 | 7 | 16 3/4 | 114 | 12 |
| 903 | L16H | D | TB41950 | 935 | - | 245 | 357 | 400 | 435 | 483 | 2.89 | 6 | 11 5/8 | 7 | 16 3/4 | 125 | 12 |

TROJAN DEEP CYCLE 8 VOLT FLOODED

| | | | | | | | | | | | | | | | | | |
|-----|-----------|---|---------|-----|-----|---|-----|-----|-----|-----|------|---|--------|-------|--------|----|----|
| GC8 | T-875 | C | TB18991 | 295 | 117 | - | 145 | 155 | 170 | 189 | 1.51 | 8 | 10 1/4 | 7 1/8 | 11 1/8 | 63 | 18 |
| GC8 | T-890 | C | TB23704 | 340 | 132 | - | 155 | 175 | 190 | 211 | 1.69 | 8 | 10 1/4 | 7 1/8 | 11 1/8 | 69 | 12 |
| GC8 | RANGER-8V | C | TB25504 | 430 | 160 | - | 169 | 186 | 204 | 225 | 1.80 | 8 | 10 3/8 | 7 1/8 | 11 3/4 | 76 | 18 |

TROJAN DEEP CYCLE 12 & 36 VOLT

| | | | | | | | | | | | | | | | | | |
|------|-----------------------|---|----------|------|-----|-----|-----|-----|-----|-----|-------|----|----------|--------|----------|-----|----|
| GC12 | T1260 | C | TB25343 | 260 | 90 | 60 | 113 | 126 | 140 | 155 | 1.86 | 12 | 12 7/8 | 7 1/8 | 10 11/16 | 78 | 12 |
| GC12 | T1275 | C | TB27404 | 280 | 102 | 70 | 120 | 134 | 150 | 166 | 1.99 | 12 | 12 7/8 | 7 1/8 | 10 11/16 | 82 | 18 |
| N/A | J150 | C | TB27053 | 280 | 102 | 70 | 120 | 134 | 150 | 166 | 1.99 | 12 | 13 15/16 | 7 1/8 | 11 1/8 | 84 | 12 |
| 921 | J185E-AC | D | TB29993 | 312 | - | 82 | 144 | 160 | 175 | 194 | 2.33 | 12 | 15 1/2 | 7 | 14 5/8 | 102 | 12 |
| 921 | J185G-AC | D | TB32480 | 324 | - | 93 | 152 | 170 | 185 | 205 | 2.46 | 12 | 15 1/2 | 7 | 14 5/8 | 106 | 12 |
| 921 | J185P-AC | D | TB35522 | 380 | - | 104 | 168 | 189 | 205 | 226 | 2.71 | 12 | 15 | 7 | 14 5/8 | 114 | 12 |
| 921 | J185H-AC | D | TB39861 | 440 | - | 121 | 185 | 207 | 225 | 249 | 2.99 | 12 | 15 | 7 | 14 5/8 | 123 | 12 |
| N/A | DC-500ML | Z | TB174209 | 1050 | - | 272 | 361 | 410 | 450 | 500 | 6.00 | 12 | 19 1/4 | 10 5/8 | 16 3/4 | 332 | 12 |
| N/A | 18-DC-500ML (36 Volt) | Z | TB503407 | 1050 | - | 272 | 361 | 410 | 450 | 500 | 18.00 | 36 | 35 1/4 | 19 1/8 | 16 3/4 | 986 | 12 |

| BCI GROUP SIZE | PART NUMBER | CORE CLASS | BIN NUMBER | RESERVE CAPACITY @ | | CRANKING | | AMPERE HOUR | | | | Kwh | VOLTAGE | MAXIMUM DIMENSIONS | | | WEIGHT LBS | WARRANTY MOS. |
|----------------|-------------|------------|------------|--------------------|-----|----------|--------|-------------|------|-------|-------|-----|---------|--------------------|-------|--------|------------|---------------|
| | | | | 25A | 75A | @ 0 F | @ 32 F | 5HR | 20HR | 100HR | 100HR | | | LENGTH | WIDTH | HEIGHT | | |

TROJAN RV / MARINE DEEP CYCLE SUPERIOR CYCLING SERIES FLOODED

| | | | | | | | | | | | | | | | | | |
|-----|--------|---|---------|-----|----|-----|-----|-----|-----|-----|------|----|----------|-------|-------|----|----|
| 24 | SCS150 | A | TB19277 | 150 | 36 | 530 | 650 | 80 | 100 | 111 | 1.33 | 12 | 11 1/4 | 6 3/4 | 9 3/4 | 50 | 12 |
| 27 | SCS200 | A | TB22053 | 200 | 52 | 620 | 760 | 95 | 115 | 128 | 1.54 | 12 | 12 3/4 | 6 3/4 | 9 3/4 | 60 | 12 |
| 30H | SCS225 | B | TB23524 | 225 | 57 | 665 | 820 | 105 | 130 | 144 | 1.73 | 12 | 13 15/16 | 6 3/4 | 10 | 66 | 12 |

TROJAN RV / MARINE DEEP CYCLE 12 VOLT FLOODED

| | | | | | | | | | | | | | | | | | |
|-----|-------|---|---------|-----|----|-----|-----|-----|-----|-----|------|----|----------|-------|---------|----|----|
| 24 | 24TMS | A | TB10908 | 100 | - | 385 | 480 | 46 | 60 | - | - | 12 | 11 1/4 | 6 3/4 | 9 3/4 | 36 | 12 |
| 24 | 24TM | A | TB11156 | 120 | - | 440 | 550 | 53 | 70 | - | - | 12 | 11 1/4 | 6 3/4 | 9 3/4 | 38 | 12 |
| 24 | 24TMX | A | TB16466 | 140 | 36 | 550 | 690 | 70 | 85 | 94 | 1.13 | 12 | 11 1/4 | 6 3/4 | 9 3/4 | 47 | 12 |
| 27 | 27TMS | A | TB12761 | 150 | - | 550 | 690 | 66 | 87 | - | - | 12 | 12 3/4 | 6 3/4 | 9 3/4 | 55 | 12 |
| 27 | 27TM | A | TB13164 | 170 | - | 660 | 825 | 80 | 105 | - | - | 12 | 12 3/4 | 6 3/4 | 9 3/4 | 55 | 12 |
| 27 | 27TMX | A | TB18294 | 175 | 45 | 530 | 650 | 85 | 105 | 117 | 1.40 | 12 | 12 3/4 | 6 3/4 | 9 3/4 | 55 | 12 |
| 27 | 27TMH | A | TB20581 | 200 | 51 | 620 | 760 | 95 | 115 | 128 | 1.54 | 12 | 12 3/4 | 6 3/4 | 9 3/4 | 61 | 12 |
| 30H | 30XHS | B | TB23396 | 225 | 57 | 665 | 820 | 105 | 130 | 144 | 1.73 | 12 | 13 15/16 | 6 3/4 | 10 1/16 | 66 | 12 |
| 31 | 31XHS | B | TB23396 | 225 | 57 | 665 | 820 | 105 | 130 | 144 | 1.73 | 12 | 13 | 6 3/4 | 9 1/2 | 67 | 12 |

| BCI GROUP SIZE | PART NUMBER | CORE CLASS | BIN NUMBER | RESERVE CAPACITY @ | | | AMPERE HOUR | | | | Kwh 100 HR | VOLTAGE | MAXIMUM DIMENSIONS INCHES | | | WEIGHT LBS | LMTD WARRANTY MOS. |
|------------------------------|-------------|------------|------------|--------------------|-----|-----|-------------|-------|-------|--------|------------|---------|---------------------------|--------|----------|------------|--------------------|
| | | | | 25A | 56A | 75A | 5 HR | 10 HR | 20 HR | 100 HR | | | LENGTH | WIDTH | HEIGHT | | |
| TROJAN DEEP CYCLE GEL | | | | | | | | | | | | | | | | | |
| GC2 | T6V-GEL | C | TB37359 | 394 | - | - | 154 | 167 | 189 | 198 | 1.19 | 6 | 10 1/4 | 7 1/8 | 10 7/8 | 68 | 12 |
| DIN | TE35-GEL | C | TB37438 | 479 | - | - | 180 | 193 | 210 | 220 | 1.32 | 6 | 9 5/8 | 7 1/2 | 10 5/8 | 69 | 12 |
| 24 | T24-GEL | A | TB28779 | 147 | - | - | 66 | 72 | 77 | 85 | 1.02 | 12 | 10 7/8 | 6 9/16 | 9 5/16 | 52 | 12 |
| 27 | T27-GEL | A | TB34669 | 179 | - | - | 76 | 84 | 91 | 100 | 1.20 | 12 | 12 13/16 | 6 3/4 | 9 1/4 | 62 | 12 |
| 30H | T31-GEL | B | TB35911 | 200 | - | - | 85 | 94 | 102 | 108 | 1.30 | 12 | 12 15/16 | 6 3/4 | 9 5/8 | 70 | 12 |
| 8D | T8D-GEL | E | TB83870 | 500 | - | - | 188 | 207 | 225 | 265 | 3.18 | 12 | 21 1/16 | 11 | 10 13/16 | 163 | 12 |
| DIN | 5SHP-GEL | D | TB42791 | 250 | - | - | 110 | 115 | 125 | 164 | 1.64 | 12 | 13 9/16 | 6 3/4 | 11 1/8 | 85 | 12 |

| | | | | | | | | | | | | | | | | | |
|--------------------------------------|----------|---|---------|---|---|---|-----|---|-----|---|---|----|-------|------|-------|-----|----|
| TROJAN RELIANT DEEP CYCLE AGM | | | | | | | | | | | | | | | | | |
| GC2 | T105-AGM | C | TB31934 | - | - | - | 171 | - | 217 | - | - | 6 | 10.30 | 7.06 | 10.73 | 68 | 12 |
| 902 | J305-AGM | D | TB51389 | - | - | - | 250 | - | 310 | - | - | 6 | 11.66 | 6.94 | 13.99 | 97 | 12 |
| 903 | L16-AGM | D | TB60509 | - | - | - | 290 | - | 370 | - | - | 6 | 11.66 | 6.94 | 16.31 | 115 | 12 |
| GC8 | T875-AGM | C | TB38120 | - | - | - | 130 | - | 160 | - | - | 8 | 10.30 | 7.06 | 10.73 | 69 | 12 |
| N/A | J185-AGM | D | TB63515 | - | - | - | 157 | - | 200 | - | - | 12 | 14.97 | 6.94 | 14.07 | 118 | 12 |

| BCI GROUP SIZE | PART NUMBER | CORE CLASS | BIN NUMBER | RESERVE CAPACITY @ | | CRANKING | | AMPERE HOUR | | | Kwh 100HR | VOLTAGE | MAXIMUM DIMENSIONS INCHES | | | WEIGHT LBS | WARRANTY MOS. |
|--------------------------------|-------------|------------|------------|--------------------|-----|-----------|-----------|-------------|------|-------|-----------|---------|---------------------------|-------|--------|------------|---------------|
| | | | | 25A | 75A | CCA @ 0 F | CA @ 32 F | 5HR | 20HR | 100HR | | | LENGTH | WIDTH | HEIGHT | | |
| TROJAN DUAL PURPOSE AGM | | | | | | | | | | | | | | | | | |
| GC2 | T6V-AGM | C | TB30588 | 385 | - | 1100 | 1400 | 154 | 200 | 221 | 1.33 | 6 | 10.28 | 7.08 | 10.74 | 65 | 12 |
| 8D | T8D-AGM | E | TB66504 | 460 | - | 1450 | 1850 | 179 | 230 | 254 | 3.05 | 12 | 20.47 | 10.64 | 9.08 | 167 | 12 |

| | | | | | | | | | | | | | | | | | |
|------------------------------|---------------|---|---------|-----|---|-----|-----|-----|-----|-----|------|----|-------|------|-------|-----|----|
| TROJAN DEEP CYCLE AGM | | | | | | | | | | | | | | | | | |
| U1 | TU1-AGM | U | TB15911 | - | - | - | - | 29 | 33 | 34 | 0.41 | 12 | 7.78 | 5.20 | 6.75 | 27 | 12 |
| 24 | T24-AGM | A | TB26316 | 137 | - | 500 | 600 | 67 | 76 | 84 | 1.01 | 12 | 10.77 | 6.84 | 8.62 | 54 | 12 |
| 27 | T27-AGM | A | TB29723 | 158 | - | 550 | 660 | 77 | 89 | 99 | 1.19 | 12 | 12.05 | 6.84 | 9.32 | 64 | 12 |
| 31 | T31-AGM | B | TB31330 | 177 | - | 600 | 720 | 82 | 100 | 111 | 1.33 | 12 | 13.44 | 6.81 | 9.18 | 69 | 12 |
| 31 | OverDrive AGM | B | TB27903 | 180 | - | 730 | 875 | 84 | 102 | 112 | 1.34 | 12 | 13.73 | 6.80 | 9.16 | 69 | 12 |
| GC12 | T12-AGM | C | TB46021 | 280 | - | 825 | 900 | 112 | 140 | 144 | 1.72 | 12 | 13.58 | 6.84 | 10.96 | 100 | 12 |

| TROJAN RENEWABLE ENERGY | | | | | | | | | | | | | | | | | |
|---------------------------------------------------------------------------------------------------------|--------------|------------|------------|-------------|-------|-------|-------|--------|--------|------------|---------|---------------------------|--------|-------|------------|--------------------|----|
| BCI GROUP SIZE | PART NUMBER | CORE CLASS | BIN NUMBER | AMPERE HOUR | | | | | | Kwh 100 HR | VOLTAGE | MAXIMUM DIMENSIONS INCHES | | | WEIGHT LBS | LMTD WARRANTY MOS. | |
| | | | | 10 HR | 20 HR | 48 HR | 72 HR | 100 HR | LENGTH | | | WIDTH | HEIGHT | | | | |
| SOLAR INDUSTRIAL LINE - DEEP-CYCLE FLOODED BATTERIES WITH SMART CARBON™ - 3,600 CYCLES @ 50% DOD | | | | | | | | | | | | | | | | | |
| N/A | SIND 06 610 | E | TB75344 | - | 421 | 472 | 540 | 578 | 610 | - | 3.66 | 6 | 15.33 | 10.22 | 24.01 | 220 | 36 |
| N/A | SIND 06 920 | E | TB109264 | - | 627 | 708 | 813 | 870 | 920 | - | 5.52 | 6 | 22.34 | 10.30 | 24.01 | 315 | 36 |
| N/A | SIND 06 1225 | E | TB140352 | - | 835 | 942 | 1083 | 1159 | 1225 | - | 7.35 | 6 | 27.13 | 10.44 | 24.01 | 415 | 36 |
| N/A | SIND 04 1685 | E | TB130405 | - | 1149 | 1293 | 1489 | 1594 | 1685 | - | 6.74 | 4 | 22.34 | 10.30 | 24.01 | 367 | 36 |
| N/A | SIND 04 2145 | E | TB161163 | - | 1474 | 1647 | 1896 | 2030 | 2145 | - | 8.58 | 4 | 27.22 | 10.44 | 24.01 | 465 | 36 |
| N/A | SIND 02 1990 | E | TB82859 | - | 1393 | 1547 | 1771 | 1889 | 1990 | - | 3.98 | 2 | 15.33 | 10.22 | 24.01 | 235 | 36 |
| N/A | SIND 02 2450 | E | TB98503 | - | 1712 | 1882 | 2166 | 2318 | 2450 | - | 4.90 | 2 | 17.33 | 10.22 | 24.01 | 278 | 36 |

| | | | | | | | | | | | | | | | | | |
|------------------------------------------------------------------------------------------------------|--------------|---|---------|---|------|------|------|------|------|---|------|---|----------|---------|----------|-----|----|
| SOLAR PREMIUM LINE - DEEP-CYCLE FLOODED BATTERIES WITH Smart Carbon™ - 1,900 CYCLES @ 50% DOD | | | | | | | | | | | | | | | | | |
| N/A | SPRE-12-225 | D | TB42549 | - | 179 | 204 | 212 | 216 | 225 | - | 2.70 | 6 | 14 65/67 | 6 81/89 | 14 49/69 | 132 | 24 |
| GC2 | SPRE-06-255 | C | TB20843 | - | 211 | 229 | 244 | 249 | 255 | - | 1.53 | 6 | 10 3/10 | 7 10/77 | 11 37/50 | 67 | 24 |
| 903 | SPRE-06-415 | D | TB43388 | - | 346 | 377 | 401 | 410 | 415 | - | 2.50 | 6 | 11 33/50 | 6 47/50 | 17 11/20 | 118 | 24 |
| 903 | SPRE-02-1255 | D | TB42295 | - | 1039 | 1130 | 1203 | 1232 | 1255 | - | 2.51 | 2 | 11 33/50 | 6 47/50 | 17 11/20 | 119 | 24 |

| | | | | | | | | | | | | | | | | | |
|---------------------------------------------------------------------------|-------------|---|---------|---|-----|-----|-----|-----|-----|---|------|----|-------|------|-------|-----|----|
| SOLAR AGM LINE - DEEP-CYCLE AGM BATTERIES - 1,700 CYCLES @ 50% DOD | | | | | | | | | | | | | | | | | |
| N/A | SAGM 12 135 | D | TB42075 | - | 131 | 135 | 136 | 137 | 137 | - | 1.62 | 12 | 12.96 | 7.06 | 10.96 | 83 | 12 |
| N/A | SAGM 12 205 | D | TB64638 | - | 174 | 205 | 210 | 213 | 216 | - | 2.46 | 12 | 14.97 | 6.94 | 14.07 | 131 | 12 |
| N/A | SAGM 08 165 | D | TB38185 | - | 145 | 165 | 168 | 171 | 174 | - | 1.32 | 8 | 10.30 | 7.06 | 10.73 | 70 | 12 |
| N/A | SAGM 06 220 | D | TB34729 | - | 190 | 220 | 228 | 231 | 235 | - | 1.32 | 6 | 10.30 | 7.06 | 10.73 | 68 | 12 |
| N/A | SAGM 06 315 | D | TB51986 | - | 278 | 315 | 326 | 331 | 335 | - | 1.89 | 6 | 11.66 | 6.94 | 13.99 | 95 | 12 |
| N/A | SAGM 06 375 | D | TB61298 | - | 329 | 375 | 389 | 394 | 400 | - | 2.25 | 6 | 11.66 | 6.94 | 16.31 | 114 | 12 |

The product descriptions, specifications and pricing were correct at the time this material was being prepared for printing. Our policy is one of continuous development and we reserve the right to change design, specifications or pricing at any time, without notice and without incurring obligation.